and Food Handling Equipment Push Handle

Insulated Proof/Hold Cabinet with Universal Supports

Your best choice for both proofing and holding



- All aluminum construction
- 3/4" concealed foam insulation provides additional energy efficiency and enhanced heat and moisture control
- Furnished with 16 pair (CA71) or 7 pair (CA39) of 5-1/2" removable universal pan supports
- Accommodates a wide range of pans and screens from 17" to 23" wide and up to 26" deep, including 18" x 26" trays and steam table pans
- Includes H-HEAT UNIT-EXT and pan stop to provide even heat distribution throughout cabinet
- Full height unit will accommodate up to 16 full size sheet pans at 3" centers smaller spacing could accommodate additional pan supports (sold separately).
- Integrated side handles on full size cabinet
- Ambient air temperature may affect heating performance
- Large Plate Series Casters 6" PU swivel, 2 w/brakes

CA71-PFIN-CD-L*



Full Door Options: (-R) Right hinge is standard, (-L) for left hinge* Clear polycarbonate or solid aluminum

Bottom mount removable heat unit for easy maintenance and repair includes external cabinet controls



Digital thermometer PROOF in face of heat unit Temp adjustable to approximately 180°F in Hold for insulated cabinets



Hold provides dry heat only while Proof provides lower temps with humidity





temperature and humidity controls

120 volt. 1500 watts. 60 cycle, single phase 8-foot power cord 3 prong plug

> Cabinet Options: Bumpers Hasp lock

Drip Pan

Dedicated 15 amp circui required

MODEL#	DOOR STYLE	CENTER SPACING	OUTSIDE DIMENSIONS H x W x D (INCHES)	SHEET PAN CAPACITY	WEIGHT (LBS.)
CA71-PFIN-CD-R	FULL CLEAR	1-1/2"	74-1/2 x 28-1/2 x 35	16	196
CA71-PFIN-CDD-R	CLEAR DUTCH	1-1/2"	74-1/2 x 28-1/2 x 35	16	201
CA71-PFIN-ID-R	FULL SOLID INSULATED	1-1/2"	74-1/2 x 28-1/2 x 35	16	206
CA71-PFIN-IDD-R	SOLID INSULATED DUTCH	1-1/2"	74-1/2 x 28-1/2 x 35	16	211
CA39-PFIN-CD-R*	CLEAR	1-1/2"	42-9/16 x 28-1/2 x 35	7	125
CA39-PFIN-ID-R*	SOLID INSULATED	1-1/2"	42-9/16 x 28-1/2 x 35	7	133

(-R) Right hinge is standard, indicate -L for left hinge. *Left hinge and/or cabinets less than full height are non-returnable.



www.lockwoodusa.com • customerservice@lockwoodusa.com